

FAVORIT

Technical Data Sheet

Favorit LITOL-24 MP2/3



Packages:
400g

[EN] Favorit LITOL-24 MP2/3 Multipurpose lithium grease, based on refined mineral oils, contains special anti-oxidative and anti-corrosive additives. It reliably protects from corrosion when the equipment is used in a humid and soiled environment for a long period of time. Water-resistant. It has a wide operating temperature range: from -30°C up to +120°C.

[RU] Favorit LITOL-24 MP2/3 Многоцелевая литиевая смазка, изготовленная на базе высокоочищенных минеральных масел, содержит специальные антиокислительные и противокоррозионные присадки. Надежно защищает от коррозии при работе оборудования во влажной и загрязненной среде в течение длительного срока эксплуатации. Вдостойка. Имеет широкий диапазон рабочих температур: от -30 до +120°C.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Color, visual	p.5.1. TC BY 690567607.022-2015	corresponds
Penetration, Worked, 25°C	GOST 5346-78 (Method B)	240
Dropping Point, °C, min.	GOST 6793-74	200
Colloidal stability, % of the selected oil, max.	GOST 7142-74 (Method A)	12,2
Tensile strength, Pa, 20 °C, min.	GOST 7143-73 (Method B)	380
Four ball method, welding load 20°C, H	GOST 9490-75	1410
Four ball method load 20°C, scuffing index, H	GOST 9490-75	310

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.

LLC "Eurasia Lubricants"

223034, Republic of Belarus, Minsky region, Zaslavl, Zavodskaya str. 1, room 3