

# FAVORIT

## Technical Data Sheet

### Favorit ТАД-17



#### Packages:

1L, 20L, 60L, 208L

#### Meets the requirements and specifications:

ГОСТ 23652-79

SAE 85W-90

API GL-5

[EN] Favorit ТАД-17 mineral-based multigrade universal transmission oil designed for lubrication of cylindrical, bevel, spiral-bevel, worm and hypoid gears of automobiles and other equipment. Provides a high level of wear protection over a wide range of loads.

[RU] Favorit ТАД-17 всесезонное универсальное трансмиссионное масло на минеральной основе, разработанное для смазывания цилиндрических, конических, спирально-конических, червячных и гипоидных передач автомобилей и другой техники. Обеспечивает высокий уровень защиты от износа в широком диапазоне нагрузок.

**Precautions:** Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

**Storage conditions:** Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

#### Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm <sup>2</sup> /c at 40 °C	STB ISO 3104-2003	160,03
Kinematic viscosity mm <sup>2</sup> /c at 100 °C	STB ISO 3104-2003	14,94
Viscosity index	STB 1797	92,29
Flash poin, °C	GOST 4333	220
Pour point, °C	GOST 20287	-20
TBN, g KOH/kg	GOST 11362	
Density at 20°C, kg/m <sup>3</sup>	GOST 3900	890

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.