

# FAVORIT

## Technical Data Sheet

### Favorit Truck FDS-5 SAE 10W-40



**Packages:**  
20L, 60L, 208L

#### Meets the requirements and specifications:

API CI-4/SL  
ACEA E7  
JASO DH-1  
CUMMINS CES 20076/20077/20078  
CATERPILLAR ECF-1-a/ECF-2  
DETROIT DIESEL DDC 93K215  
MB 228.1/228.3  
MAN M 3275-1  
MACK EO-M Plus/EO-N  
RENAULT RLD-2  
MTU Type 2  
VOLVO VDS-3

#### Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm <sup>2</sup> /c at 40 °C	STB ISO 3104-2003	86,18
Kinematic viscosity mm <sup>2</sup> /c at 100 °C	STB ISO 3104-2003	13,75
Viscosity index	STB 1797	163
Flash poin, °C	GOST 4333	234
Pour point, °C	GOST 20287	-36
TBN, g KOH/kg	GOST 11362	10,9
Density at 20°C, kg/m <sup>3</sup>	GOST 3900	854,1

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.  
Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.  
Показатели могут варьироваться в пределах допустимой нормы.

LLC "Eurasia Lubricants"

223034, Republic of Belarus, Minsky region, Zaslavl, Zavodskaya str. 1, room 3

[EN] FAVORIT TRUCK FDS-5 SAE 10W-40 engine oil is designed for all types of heavy-duty diesel engines that meet Euro I - IV requirements. Modern additive package provides excellent anti-wear properties. The oil has increased thermal and oxidative stability and excellent detergent and dispersant properties. May be used in gasoline engines where API SL or lower performance levels are required. Manufactured according to TU BY 690567607.020-2015

[RU] Моторное масло FAVORIT TRUCK FDS-5 SAE 10W-40 предназначено для всех видов высоконагруженных дизельных двигателей, соответствующих требованиям Euro I – IV. Современный пакет присадок обеспечивает отличные противоизносные свойства. Масло обладает повышенной термоокислительной стабильностью и превосходными моюще-диспергирующими свойствами. Может быть использовано в бензиновых двигателях, где необходим уровень эксплуатационных свойств API SL или ниже. Изготовлено по ТУ BY 690567607.020-2015

**Precautions:** Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

**Storage conditions:** Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.