

FAVORIT

Technical Data Sheet

Favorit ТЭП-15



Packages:
20L, 60L, 208L

Meets the requirements and specifications:
API GL-2

[EN] Favorit ТЭП is an all-season mineral-based transmission oil based on API GL-2 for tractors and other agricultural machinery.

[RU] Favorit ТЭП всесезонное трансмиссионное масло на минеральной основе уровня API GL-2 для тракторов и другой сельскохозяйственной техники.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	163,6
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	14,25
Viscosity index	STB 1797	81,36
Flash poin, °C	GOST 4333	220
Pour point, °C	GOST 20287	-15
TBN, g KOH/kg	GOST 11362	
Density at 20°C, kg/m ³	GOST 3900	910

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.