

## Technical Data Sheet

### Favorit ATF D II



#### Packages:

1L, 4L, 20L, 60L, 208L

#### Meets the requirements and specifications:

Allison C4 Caterpillar TO-2 GM  
Dexron II D MAN 339 V1/Z1 MB  
236.5/236.7 Renk Voith G607 ZF TE-  
ML 03D/04D/11A/14A/17C

[EN] Favorit ATF D II is a multipurpose multigrade oil for automatic transmissions, hydraulic steering systems and hydraulic clutch. Provides stable operation of hydraulic systems and automatic transmissions even at temperature differences and difficult operating conditions.

[RU] Favorit ATF D II всепогодное универсальное масло, предназначенное для использования в автоматических коробках передач, гидравлических системах рулевого управления и гидравлических сцеплениях автомобилей. Обеспечивает стабильную работу гидравлических систем и АКПП даже при перепадах температур и сложнейших условий эксплуатации.

**Precautions:** Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

**Storage conditions:** Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

#### Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm <sup>2</sup> /c at 40 °C	STB ISO 3104-2003	6,15
Kinematic viscosity mm <sup>2</sup> /c at 100 °C	STB ISO 3104-2003	31,46
Viscosity index	STB 1797	147,73
Flash poin, °C	GOST 4333	220
Pour point, °C	GOST 20287	-40
Density at 20°C, kg/m <sup>3</sup>	GOST 3900	860

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.