

FAVORIT

Technical Data Sheet

Favorit Diesel M10Г2К-М API CC



Packages:

5L, 20L, 60L, 208L

Meets the requirements and specifications:

API CC

SAE 30

[EN] Favorit Diesel M10Г2К-М API CC mineral-based monograde oil, designed for use in summer period of domestic production highly accelerated diesel engines with moderate supercharging and naturally aspirating of trucks, agricultural and roadway construction equipment. It has excellent antioxidant, anti-corrosion and anti-wear characteristics, has good detergent-dispersant properties. Viscosity grade SAE 30.

[RU] Favorit Diesel M10Г2К-М API CC масло сезонное на минеральной основе, предназначенное для летней эксплуатации высокофорсированных дизельных двигателях отечественного производства с умеренным наддувом и без наддува грузовых автомобилей, сельскохозяйственной и дорожно-строительной техники. Имеет отличные антиокислительные, антикоррозионные и противоизносные характеристики, обладает хорошими моюще-диспергирующими свойствами. Класс вязкости SAE 30.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	86,43
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	10,5
Viscosity index	STB 1797	98,87
Flash poin, °C	GOST 4333	
Pour point, °C	GOST 20287	
TBN, g KOH/kg	GOST 11362	
Density at 20°C, kg/m ³	GOST 3900	875

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.