

FAVORIT

Technical Data Sheet

Favorit Flush FLX SAE 10



Packages:
4L, 20L, 60L, 208L

[EN] Favorit Flush FLX SAE 10 low viscosity mineral oil with excellent detergent properties. Effectively removes oxidation and wear products. Designed for washing oil sumps and lubricating systems of internal combustion engines. It can also be used to flush transmissions and gearboxes.

[RU] Favorit Flush FLX SAE 10 минеральное масло, характеризующееся низкой вязкостью и обладающее отличными моющими свойствами. Эффективно удаляет продукты окисления и износа. Предназначено для промывки масляных отстойников и смазывающих систем двигателей внутреннего сгорания. Оно может также использоваться для промывки трансмиссий и коробок передач.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	38,07
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	6,2
Viscosity index	STB 1797	109,71
Flash poin, °C	GOST 4333	206
Pour point, °C	GOST 20287	-15
TBN, g KOH/kg	GOST 11362	0,6
Density at 20°C, kg/m ³	GOST 3900	870

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.