

FAVORIT

Technical Data Sheet

Favorit Moto 4T SAE 20W-50 API SG/CD



Packages:

1L, 4L, 10L, 20L, 60L, 208L

Meets the requirements and specifications:

SAE 20W-50

API SG/CD

JASO MA2

[EN] Favorit Moto 4T SAE 20W-50 API SG/CD is a mineral motor oil intended for use in four-stroke gasoline engines of modern motorcycles, quadrunners, scooters and other motor vehicles with air and water cooling, as well as for four-stroke engines of lawn mowers, generators, cultivators, motor pumps and other garden equipment. Prevents engine wear, prevents the formation of carbon deposits and varnish deposits, guarantees a reliable oil film.

[RU] Favorit Moto 4T SAE 20W-50 API SG/CD минеральное моторное масло, предназначенное для использования в четырехтактных бензиновых двигателях современных мотоциклов, квадроциклов, скутеров и прочей мототехники с воздушным и водяным охлаждением, а также для четырехтактных двигателей газонокосилок, генераторов, культиваторов, мотопомп и другого садового оборудования. Предотвращает износ двигателя, препятствует образованию нагара и лаковых отложений, гарантирует надежную масляную пленку.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	162.92
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	17.84
Viscosity index	STB 1797	120.66
Flash poin, °C	GOST 4333	235
Pour point, °C	GOST 20287	-27
TBN, g KOH/kg	GOST 11362	6,1
Density at 20°C, kg/m ³	GOST 3900	885

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.

LLC "Eurasia Lubricants"

223034, Republic of Belarus, Minsky region, Zaslavl, Zavodskaya str. 1, room 3