

FAVORIT

Technical Data Sheet

Favorit HD 50 SAE 50 API CH-4



Packages:

10L, 20L, 60L, 208L

Meets the requirements and specifications:

SAE 50

API CH-4

[EN] Favorit HD 50 SAE 50 API CH-4 Mineral-based monograde oil for diesel engines. Balanced viscosity characteristics are for summer use. An effective package of functional additives with high antiwear, antioxidant, detergent and dispersant properties.

[RU] Favorit HD 50 SAE 50 API CH-4 сезонное масло на минеральной основе, предназначенное для дизельных двигателей. Сбалансированные вязкостные характеристики для применения в летний период. Эффективный пакет функциональных присадок с высокими противоизносными, антиокислительными, моющими и диспергирующими свойствами.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	158,1
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	17,39
Viscosity index	STB 1797	120
Flash point, °C	GOST 4333	224
Pour point, °C	GOST 20287	-18
Density at 20°C, kg/m ³	GOST 3900	882

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.