

FAVORIT

Technical Data Sheet

Favorit Super DI SAE 10W-40 API CF-4/SG



Packages:

1L, 4L, 5L, 20L, 60L, 208L

Meets the requirements and specifications:

SAE 10W-40
API CF-4/SG

[EN] Favorit Super DI SAE 10W-40 API CF-4/SG multipurpose multigrade semi-synthetic engine oil designed for diesel engines. It can be used in gasoline engines. It has high resistance to aging. Effectively reduces carbon and varnish formation. Provides reliable lubrication of engine parts. It provides superior wear protection regardless of operating conditions, ensuring extended engine life.

[RU] Favorit Super DI SAE 10W-40 API CF-4/SG всепогодное универсальное полусинтетическое моторное масло, предназначенное для дизельных двигателей. Возможно использование в бензиновых двигателях. Обладает высокой стойкостью к старению. Эффективно снижает нагаро- и лакообразование. Обеспечивает надежную смазку деталей двигателя. Превосходная защита от износа независимо от условий эксплуатации, гарантирующая увеличенный срок службы двигателя.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	108,17
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	13,66
Viscosity index	STB 1797	125,29
Flash poin, °C	GOST 4333	226
Pour point, °C	GOST 20287	-27
TBN, g KOH/kg	GOST 11362	6,4
Density at 20°C, kg/m ³	GOST 3900	880

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.